

TYRES

Product group	Tyres
Item number	17466448
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	160 K (158 L)
TL/TT	TL
Brand	Nokian
Tread pattern	R-Truck Trailer



Notes and features

- The Nokian R-Truck Trailer is an all-season truck trailer tyre for mixed use on roads and building sites, caravans and forestry trailers.
- Its non-directional tread pattern with coarse tread blocks offers good on-road performance and good off-road self-cleaning properties.
- Its cut-resistant rubber compound protects the tyre from damages on difficult surfaces.
- The design of the main grooves with stone ejectors prevents small stones from penetrating the tyre and thus reduces the risk of punctures.
- All R-Truck tyres are characterised by very good puncture protection, even in the toughest conditions.
- When on the road, R-Truck tyres are particularly quiet and have a low rolling resistance.

Technical Informations

Item number	17466448
EAN	6419440314532
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	160 K (158 L)
TL/TT	TL
Brand	Nokian
Tread pattern	R-Truck Trailer
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	C
Wet grip	B
Rolling noise [db].	74
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	75,00
Recommended rim size	11.75
Permitted rim size	12.25
Maximum air pressure [bar].	9,00
Section width (mm)	389
Outer diameter of tyre [mm].	1072
Stat. radius (SLR) [mm]	496
Rolling circumference [mm].	3258
Tread depth (mm)	15,0

E-Ready No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 K	4500	110	Single	9,00	
158 L	4250	120	Single	9,00	