

## **TYRES**

Product group	Tyres	
Item number	17466449	
Valid tyre size	385 / 65 R 22.5	
LI / SI / PR	160 K (158 L)	
TL/TT	TL	
Brand	Nokian	
Tread pattern	Hakka Truck Trailer	



## **Technical Informations**

Item number	17466449
EAN	6419440453460
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	160 K (158 L)
TL/TT	TL
Brand	Nokian
Tread pattern	Hakka Truck Trailer
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	В

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Wet grip	С
Rolling noise [db].	67
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	74,00
Recommended rim size	11.75
Permitted rim size	12.25
Maximum air pressure [bar].	9,00
Section width (mm)	380
Outer diameter of tyre [mm].	1084
Stat. radius (SLR) [mm]	501
Rolling circumference [mm].	3295
Tread depth (mm)	15,5
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 K	4500	110	Single	9,00	
158 L	4250	120	Single	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.