

## TYRES

|                 |                 |
|-----------------|-----------------|
| Product group   | Tyres           |
| Item number     | 17466452        |
| Valid tyre size | 385 / 65 R 22.5 |
| LI / SI / PR    | 160 K           |
| TL/TT           | TL              |
| Brand           | Nokian          |
| Tread pattern   | E-Truck Steer   |



Bohnenkamp  
■ ■ ● Moving Professionals

## Notes and features

- The Nokian E-Truck is an all-season tyre for truck steer axles or buses used in regional and long-distance transport.
- Thanks to its spiral-shaped sipes, the tyre ensures very good handling on wet roads.
- Its special zigzag-shaped grooves eject small stones and prevent damage.
- The tread pattern wears evenly and ensures a long service life for the tyre.

## Technical Informations

|                              |                 |
|------------------------------|-----------------|
| Item number                  | 17466452        |
| EAN                          | 6419440383064   |
| Valid tyre size              | 385 / 65 R 22.5 |
| LI / SI / PR                 | 160 K           |
| TL/TT                        | TL              |
| Brand                        | Nokian          |
| Tread pattern                | E-Truck Steer   |
| M+S                          | M+S             |
| 3PMSF                        | 3PMSF           |
| Axle position truck          | FA              |
| Rolling resistance           | C               |
| Wet grip                     | B               |
| Rolling noise [db].          | 71              |
| Rolling noise level          | A               |
| Antistatic                   | No              |
| Tyre colour                  | Black           |
| ECE regulation number        | ECE 54,ECE 117  |
| Nettogewicht [kg] (gültig)   | 69,80           |
| Recommended rim size         | 11.75           |
| Permitted rim size           | 12.25           |
| Maximum air pressure [bar].  | 9,00            |
| Section width (mm)           | 378             |
| Outer diameter of tyre [mm]. | 1078            |
| Stat. radius (SLR) [mm]      | 479             |
| Rolling circumference [mm].  | 3277            |
| Tread depth (mm)             | 13,5            |

E-Ready

No

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 160 K | 4500               | 110          | Single        | 9,00                     |              |