

TYRES

Product group	Tyres
Item number	17466453
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	164 K
TL/TT	TL
Brand	Nokian
Tread pattern	R-Truck Steer XL



Technical Informations

Item number	17466453
EAN	6419440431451
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	164 K
TL/TT	TL
Brand	Nokian
Tread pattern	R-Truck Steer XL
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	С

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Wet grip	С
Rolling noise [db].	70
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	80,40
Recommended rim size	11.75
Permitted rim size	12.25
Maximum air pressure [bar].	9,00
Section width (mm)	381
Outer diameter of tyre [mm].	1086
Stat. radius (SLR) [mm]	502
Rolling circumference [mm].	3301
Tread depth (mm)	16,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 K	5000	110	Single	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.