

TYRES

Product group	Tyres	
Item number	17466520	
Valid tyre size	315 / 80 R 22.5	
LI / SI / PR	156 / 150 L (154 / 150 M)	
TL/TT	TL	
Brand	Nokian	
Tread pattern	E-Truck Steer	



Notes and features

- The Nokian E-Truck is an all-season tyre for truck steer axles or buses used in regional and long-distance transport.
- Thanks to its spiral-shaped sipes, the tyre ensures very good handling on wet roads.
- Its special zigzag-shaped grooves eject small stones and prevent damage.
- The tread pattern wears evenly and ensures a long service life for the tyre.



Technical Informations

Item number	17466520
EAN	6419440247779
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 150 L (154 / 150 M)
TL/TT	TL
Brand	Nokian
Tread pattern	E-Truck Steer
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	С
Wet grip	A
Rolling noise [db].	69
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	68,00
Recommended rim size	9.00
Maximum air pressure [bar].	8,50
Section width (mm)	314
Outer diameter of tyre [mm].	1071
Stat. radius (SLR) [mm]	498
Rolling circumference [mm].	3255
Tread depth (mm)	14,5
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 L	4000	120	Single	8,50	
154 M	3750	130	Single	8,50	
150 L	3350	120	Twin	8,50	
150 M	3350	130	Twin	8,50	