Bohnenkamp Moving Professionals

14.11.2024

TYRES

Product group	Tyres	
Item number	18365350	
Valid tyre size	6.00 - 16	
LI / SI / PR	95 / 92 L, 6 PR	
TL/TT	TL	
Brand	Security	
Tread pattern	ML914	



Technical Informations

Item number	18365350
EAN	4040658018022
Valid tyre size	6.00 - 16
LI / SI / PR	95 / 92 L, 6 PR
TL/TT	TL
Brand	Security
Tread pattern	ML914
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	12,00

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Recommended rim size	4.50
Maximum air pressure [bar].	4,00
Section width (mm)	170
Outer diameter of tyre [mm].	730
Rolling circumference [mm].	2300
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
95 L	690	120		4,00	
92 L	630	120		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.