

TYRES

Product group	Tyres	
Item number	18366121	
Valid tyre size	155 / 70 R 12 C	
LI / SI / PR	104 / 102 N	
TL/TT	TL	
Brand	Security	
Tread pattern	TR603	



Notes and features

- The Security TR 603 is a professional tyre for use on car trailers.
- The tyre is reinforced by additional casing plies and offers very good stability.



Technical Informations

Item number	18366121
EAN	4260399943142
Valid tyre size	155 / 70 R 12 C
LI / SI / PR	104 / 102 N
TL/TT	TL
Brand	Security
Tread pattern	TR603
M+S	M+S
Rolling resistance	D
Wet grip	С
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	8,00
Recommended rim size	4.50J
Maximum air pressure [bar].	6,30
Section width (mm)	157
Outer diameter of tyre [mm].	523
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
104 N	900	140		6,30	
102 N	850	140		6,30	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.