Bohnenkamp Moving Professionals

20.09.2024

TYRES

Product group	Tyres
Item number	18366151
Valid tyre size	165 R 13 C
LI / SI / PR	96 N (94 / 92 R)
TL/TT	TL
Brand	Security
Tread pattern	TR603



Notes and features

- The Security TR 603 is a professional tyre for use on car trailers.
- The tyre is reinforced by additional casing plies and offers very good stability.

Bohnenkamp Moving Professionals

Technical Informations

Item number	18366151
EAN	4040658065316
Valid tyre size	165 R 13 C
LI / SI / PR	96 N (94 / 92 R)
TL/TT	TL
Brand	Security
Tread pattern	TR603
M+S	M+S
Rolling resistance	D
Wet grip	C
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	9,00
Recommended rim size	4.50
Maximum air pressure [bar].	4,50
Section width (mm)	165
Outer diameter of tyre [mm].	594
Stat. radius (SLR) [mm]	278
Rolling circumference [mm].	1806
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
96 N	710	140		4,50	
94 R	670	170		4,50	
92 R	630	170		4,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.