

## **TYRES**

Product group	Tyres	
Item number	18366207	
Valid tyre size	185 R 14 C	
LI / SI / PR	102 / 100 S (104 N), 8 PR	
TL/TT	TL	
Brand	Security	
Tread pattern	TR603	



## **Notes and features**

- The Security TR 603 is a professional tyre for use on car trailers.
- The tyre is reinforced by additional casing plies and offers very good stability.



## **Technical Informations**

Item number	18366207
EAN	4260399943210
Valid tyre size	185 R 14 C
LI / SI / PR	102 / 100 S (104 N), 8 PR
TL/TT	TL
Brand	Security
Tread pattern	TR603
M+S	M+S
Rolling resistance	D
Wet grip	С
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	9,10
Recommended rim size	5.50J
Permitted rim size	5J, 6J
Maximum air pressure [bar].	4,50
Section width (mm)	188
Outer diameter of tyre [mm].	652
Stat. radius (SLR) [mm]	303
Rolling circumference [mm].	1970
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
102 S	850	180		4,50	
104 N	900	140		4,50	
100 S	800	180		4,50	