

TYRES

Product group	Tyres	
Item number	18366360	
Valid tyre size	205 R 14 C	
LI / SI / PR	109 / 107 Q, 8 PR	
TL/TT	TL	
Brand	Security	
Tread pattern	TR603	



Notes and features

- The Security TR 603 is a professional tyre for use on car trailers.
- The tyre is reinforced by additional casing plies and offers very good stability.



Technical Informations

Item number	18366360
EAN	4040658018091
Valid tyre size	205 R 14 C
LI / SI / PR	109 / 107 Q, 8 PR
TL/TT	TL
Brand	Security
Tread pattern	TR603
M+S	M+S
Rolling resistance	D
Wet grip	С
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	10,70
Recommended rim size	6J
Permitted rim size	5.503
Maximum air pressure [bar].	4,50
Section width (mm)	208
Outer diameter of tyre [mm].	686
Stat. radius (SLR) [mm]	317
Rolling circumference [mm].	2079
Tread depth (mm)	9,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
109 Q	1030	160		4,50	
113 N	1150	140		4,50	
107 Q	975	160		4,50	
109 N	1030	140		4,50	