

TYRES

Product group	Tyres	
Item number	18366370	
Valid tyre size	195 / 70 R 15 C	
LI / SI / PR	104 / 102 R (108 N), 8 PR	
TL/TT	TL	
Brand	Security	
Tread pattern	TR603	



Notes and features

- The Security TR 603 is a professional tyre for use on car trailers.
- The tyre is reinforced by additional casing plies and offers very good stability.



Technical Informations

Item number	18366370	
EAN	4260399943241	
Valid tyre size	195 / 70 R 15 C	
LI / SI / PR	104 / 102 R (108 N), 8 PR	
TL/TT	TL	
Brand	Security	
Tread pattern	TR603	
M+S	M+S	
Rolling resistance	D	
Wet grip	С	
Rolling noise [db].	72	
Rolling noise level	В	
Antistatic	No	
Tyre colour	Black	
ECE regulation number	ECE 54,ECE 117	
Nettogewicht [kg] (gültig)	10,70	
Recommended rim size	63	
Maximum air pressure [bar].	4,50	
Section width (mm)	201	
Outer diameter of tyre [mm].	655	
Stat. radius (SLR) [mm]	300	
Rolling circumference [mm].	1985	
E-Ready	No	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
104 R	900	170		4,50	
108 N	1000	140		4,50	
102 R	850	170		4,50	