

TYRES

Product group	Tyres	
Item number	18545015	
Valid tyre size	195 / 55 R 10 C	
LI / SI / PR	98 / 96 N	
TL/TT	TL	
Brand	BK Trailer	
Tread pattern	204	



Notes and features

- Reinforced sidewall design.
- The special flat tread design for trailer & caravan use ensures optimum running smoothness and driving stability.
- Low abrasion due to a special rubber compound.
- Increased payload.



Technical Informations

Item number	18545015
EAN	4040658078729
Valid tyre size	195 / 55 R 10 C
LI / SI / PR	98 / 96 N
TL/TT	TL
Brand	BK Trailer
Tread pattern	204
M+S	M+S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	6,10
Recommended rim size	6.001
Permitted rim size	6.501
Maximum air pressure [bar].	6,20
Section width (mm)	201
Outer diameter of tyre [mm].	468
Stat. radius (SLR) [mm]	213
Rolling circumference [mm].	1418
Tread depth (mm)	6,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
98 N	750	140		6,20	
96 N	710	140		6,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.