Bohnenkamp Moving Professionals

20.09.2024

TYRES

| Product group | Tyres | |
|-----------------|---------------|--|
| Item number | 18545020 | |
| Valid tyre size | 145 / 80 R 13 | |
| LI / SI / PR | 78 N | |
| TL/TT | TL | |
| Brand | BK Trailer | |
| Tread pattern | 201 | |



Notes and features

- Reinforced sidewall design.
- The special flat tread design for trailer & caravan use ensures optimum running smoothness and driving stability.
- Low abrasion due to a special rubber compound.
- Increased payload.

Bohnenkamp Moving Professionals

Technical Informations

| Item number 18545020 | | | |
|--|---------------------------------------|--|--|
| EAN 4040658065637 | 18545020 | | |
| | 4040658065637 | | |
| Valid tyre size 145 / 80 R 13 | | | |
| LI / SI / PR 78 N | | | |
| TL/TT TL | | | |
| Brand BK Trailer | | | |
| Tread pattern 201 | | | |
| M+S M+S | | | |
| Rolling resistance D | | | |
| Wet grip D | | | |
| Rolling noise [db]. 71 | | | |
| Rolling noise level B | | | |
| Antistatic No | | | |
| Tyre colour Black | | | |
| ECE regulation number ECE 30,ECE 117 | ECE 30,ECE 117 | | |
| Nettogewicht [kg] (gültig) 4,90 | | | |
| Recommended rim size 4J | 4J | | |
| Permitted rim size 3.50B, 3.50J, 4.00B, 4.50J, 4.50B, 5J | 3.50B, 3.50J, 4.00B, 4.50J, 4.50B, 5J | | |
| Maximum air pressure [bar]. 2,80 | | | |
| Section width (mm) 145 | | | |
| Outer diameter of tyre [mm]. 562 | | | |
| Stat. radius (SLR) [mm] 255 | 255 | | |
| Rolling circumference [mm]. 1714 | | | |
| Tread depth (mm) 5,0 | | | |
| E-Ready No | | | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 78 N | 425 | 140 | | 2,80 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.