

TYRES

Product group	Tyres
Item number	18545050
Valid tyre size	175 / 70 R 13
LI / SI / PR	86 N
TL/TT	TL
Brand	BK Trailer
Tread pattern	202



Bohnenkamp
Moving Professionals

Notes and features

- Reinforced sidewall design.
- The special flat tread design for trailer & caravan use ensures optimum running smoothness and driving stability.
- Low abrasion due to a special rubber compound.
- Increased payload.

Technical Informations

Item number	18545050
EAN	4040658065675
Valid tyre size	175 / 70 R 13
LI / SI / PR	86 N
TL/TT	TL
Brand	BK Trailer
Tread pattern	202
M+S	M+S
Rolling resistance	D
Wet grip	D
Rolling noise [db].	71
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 30,ECE 117
Nettogewicht [kg] (gültig)	6,60
Recommended rim size	5J
Permitted rim size	4.50B, 4.50J, 5.50J, 5.50B, 6J, 6.00B
Maximum air pressure [bar].	2,90
Section width (mm)	177
Outer diameter of tyre [mm].	576
Stat. radius (SLR) [mm]	261
Rolling circumference [mm].	1757
Tread depth (mm)	5,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
86 N	530	140		2,90	