

TYRES

Product group	Tyres	
Item number	18545090	
Valid tyre size	185 R 14 C	
LI / SI / PR	104 / 102 N	
TL/TT	TL	
Brand	BK Trailer	
Tread pattern	203	



Notes and features

- Reinforced sidewall design.
- The special flat tread design for trailer & caravan use ensures optimum running smoothness and driving stability.
- Low abrasion due to a special rubber compound.
- Increased payload.



Technical Informations

Item number	18545090
EAN	4040658065705
Valid tyre size	185 R 14 C
LI / SI / PR	104 / 102 N
TL/TT	TL
Brand	BK Trailer
Tread pattern	203
M+S	M+S
Rolling resistance	D D
	D
Wet grip	
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	9,10
Recommended rim size	5.5J
Permitted rim size	5J, 6J
Maximum air pressure [bar].	4,48
Section width (mm)	188
Outer diameter of tyre [mm].	650
Stat. radius (SLR) [mm]	295
Rolling circumference [mm].	1979
Tread depth (mm)	6,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
104 N	900	140		4,48	
102 N	850	140		4,50	