

TYRES

Product group	Tyres	
Item number	18545335	
Valid tyre size	155 / 80 R 13	
LI / SI / PR	84 N	
TL/TT	TL	
Brand	Boka Trailer Line	
Tread pattern	FT 01	





Notes and features

- Increased payload, especially for use with caravans and trailers.
- Reinforced sidewall design.
- Special tread pattern design for stable driving behaviour.



Technical Informations

Item number	18545335
EAN	4040658085383
Valid tyre size	155 / 80 R 13
LI / SI / PR	84 N
TL/TT	TL
Brand	Boka Trailer Line
Tread pattern	FT 01
M+S	M+S
Rolling resistance	D
Wet grip	С
Rolling noise [db].	71
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 30,ECE 117
Nettogewicht [kg] (gültig)	5,08
Recommended rim size	4.50
Maximum air pressure [bar].	3,00
Section width (mm)	162
Outer diameter of tyre [mm].	578
Tread depth (mm)	6,1
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
84 N	500	140		3,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.