

TYRES

| Product group | Tyres | |
|-----------------|-------------------|--|
| Item number | 18545370 | |
| Valid tyre size | 185 / 65 R 14 | |
| LI / SI / PR | 93 N TL | |
| TL/TT | | |
| Brand | Boka Trailer Line | |
| Tread pattern | FT 01 | |





Notes and features

- Increased payload, especially for use with caravans and trailers.
- Reinforced sidewall design.
- Special tread pattern design for stable driving behaviour.



Technical Informations

| Item number | 18545370 |
|------------------------------|-------------------|
| EAN | 4040658085406 |
| Valid tyre size | 185 / 65 R 14 |
| LI / SI / PR | 93 N |
| TL/TT | TL |
| Brand | Boka Trailer Line |
| Tread pattern | FT 01 |
| M+S | M+S |
| Rolling resistance | D |
| Wet grip | С |
| Rolling noise [db]. | 71 |
| Rolling noise level | В |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 30,ECE 117 |
| Nettogewicht [kg] (gültig) | 7,10 |
| Recommended rim size | 5.50 |
| Maximum air pressure [bar]. | 3,40 |
| Section width (mm) | 189 |
| Outer diameter of tyre [mm]. | 596 |
| Rolling circumference [mm]. | 1869 |
| Tread depth (mm) | 6,0 |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 93 N | 650 | 140 | | 3,40 | |