Bohnenkamp Moving Professionals

13.11.2024

TYRES

Product group	Tyres
Item number	18692435
Valid tyre size	5.0 - 10
LI / SI / PR	8 PR
TL/TT	TL
Brand	Trelleborg
Tread pattern	T462





Notes and features

- The Trelleborg T462 is a tyre for agro-industrial applications.
- Its traction tread pattern with angled lugs provides good traction on all soils.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	18692435
EAN	8059971018929
Valid tyre size	5.0 - 10
LI / SI / PR	8 PR
TL/TT	TL
Brand	Trelleborg
Tread pattern	T462
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	6,65
Recommended rim size	4.00
Permitted rim size	3.50
Maximum air pressure [bar].	5,20
Section width (mm)	144
Outer diameter of tyre [mm].	537
Rolling circumference [mm].	1571
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	670	30		5,20	