

TYRES

Product group	Tyres
Item number	18692564
Valid tyre size	320 / 60 - 12
LI / SI / PR	132 A8
TL/TT	TT
Brand	Trelleborg
Tread pattern	T421



Bohnenkamp
Moving Professionals



Notes and features

- Low-pressure tyre with low ground pressure developed for use in fields with maximum soil protection.
- Unique bias-belt design maximises ground contact area.
- Improved flotation and traction.
- Rounded shoulder ensures minimised soil compaction.

Technical Informations

Item number	18692564
EAN	8059971018295
Valid tyre size	320 / 60 - 12
LI / SI / PR	132 A8
TL/TT	TT
Brand	Trelleborg
Tread pattern	T421
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	18,60
Recommended rim size	10.50I
Maximum air pressure [bar].	4,00
Section width (mm)	320
Outer diameter of tyre [mm].	690
Stat. radius (SLR) [mm]	298
Rolling circumference [mm].	2049
Tread depth (mm)	15,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
132 A8	2000	40		4,00	