Bohnenkamp Moving Professionals

16.11.2024

TYRES

Product group	Tyres
Item number	18692698
Valid tyre size	100 / 100 - 4
LI / SI / PR	60 A8
TL/TT	тт
Brand	Trelleborg
Tread pattern	T539





Notes and features

• Combination tread pattern for green areas, agriculture, industrial or high-speed operations.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	18692698
EAN	8059971018417
Valid tyre size	100 / 100 - 4
LI / SI / PR	60 A8
TL/TT	Π
Brand	Trelleborg
Tread pattern	Т539
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	1,33
Recommended rim size	2.50
Maximum air pressure [bar].	6,00
Section width (mm)	98
Outer diameter of tyre [mm].	304
Rolling circumference [mm].	903
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
60 A8	250	40		6,00	