Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	19110039	
Valid tyre size	4.10 / 3.50 - 4	
LI / SI / PR	32 A6 / 44 A6, 4 PR	
TL/TT	TL	
Brand	Deli	
Tread pattern	S-366	



Notes and features

- The Deli S-366 was specially developed for use on lawns.
- Its block tread pattern allows it to be used on both the driven and non-driven axle and is gentle on the grass surface.
- The tyre is perfect for ride-on mowers, small machines and small transporters.

Bohnenkamp Moving Professionals

Technical Informations

Item number	19110039
EAN	8994242026930
Valid tyre size	4.10 / 3.50 - 4
LI / SI / PR	32 A6 / 44 A6, 4 PR
TL/TT	TL
Brand	Deli
Tread pattern	S-366
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	1,12
Recommended rim size	2.50
Maximum air pressure [bar].	3,50
Section width (mm)	95
Outer diameter of tyre [mm].	275
Stat. radius (SLR) [mm]	118
Rolling circumference [mm].	807
Tread depth (mm)	3,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
32 A6	112	30	Drive Wheel	3,50	
44 A6	160	30	Free Rolling	3,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.