

## **TYRES**

| Product group   | Tyres               |  |
|-----------------|---------------------|--|
| Item number     | 19110089            |  |
| Valid tyre size | 220 / 50 - 6        |  |
| LI / SI / PR    | 62 A8 / 73 A8, 6 PR |  |
| TL/TT           | ТТ                  |  |
| SET             | Tube                |  |
| Brand           | Deli                |  |
| Tread pattern   | S-317               |  |



## **Notes and features**

• Tyres with grooved tread.

Particularly suitable for use in gardening and landscaping.



## **Technical Informations**

| Item number                  | 19110089            |
|------------------------------|---------------------|
| EAN                          | 8994242027180       |
| Valid tyre size              | 220 / 50 - 6        |
| LI / SI / PR                 | 62 A8 / 73 A8, 6 PR |
| TL/TT                        | TT                  |
| SET                          | Tube                |
| Valve designation            | TR 13               |
| Ventilposition               | lateral             |
| Brand                        | Deli                |
| Tread pattern                | S-317               |
| Antistatic                   | No                  |
| Tyre colour                  | Black               |
| ECE regulation number        | ECE 106             |
| Nettogewicht [kg] (gültig)   | 3,23                |
| Recommended rim size         | 7.00                |
| Maximum air pressure [bar].  | 2,80                |
| Section width (mm)           | 220                 |
| Outer diameter of tyre [mm]. | 382                 |
| Stat. radius (SLR) [mm]      | 174                 |
| Rolling circumference [mm].  | 1119                |
| Tread depth (mm)             | 4,0                 |
| E-Ready                      | No                  |



## **Load capacity**

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 62 A8 | 265                | 40           | Drive Wheel   | 2,80                        |              |
| 73 A8 | 365                | 40           | Free Rolling  | 2,80                        |              |