Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	19110114	
Valid tyre size	4.80 / 4.00 - 8	
LI / SI / PR	31 A6 / 43 A6, 4 PR	
TL/TT	TL	
Brand	Deli	
Tread pattern	S-247	



Notes and features

• Agricultural tyre with traction tread pattern.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	19110114
EAN	8994242015484
Valid tyre size	4.80 / 4.00 - 8
LI / SI / PR	31 A6 / 43 A6, 4 PR
TL/TT	TL
Brand	Deli
Tread pattern	S-247
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	2,35
Recommended rim size	3.75
Maximum air pressure [bar].	2,10
Section width (mm)	115
Outer diameter of tyre [mm].	417
Stat. radius (SLR) [mm]	190
Rolling circumference [mm].	1241
Tread depth (mm)	8,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
31 A6	109	30	Drive Wheel	2,10	
43 A6	155	30	Free Rolling	2,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.