# Bohnenkamp Moving Professionals

TYRES

| Product group   | Tyres               |  |
|-----------------|---------------------|--|
| Item number     | 19110132            |  |
| Valid tyre size | 16 x 6.50 - 8       |  |
| LI / SI / PR    | 52 A6 / 64 A6, 4 PR |  |
| TL/TT           | TT                  |  |
| SET             | Tube                |  |
| Brand           | Deli                |  |
| Tread pattern   | S-365               |  |



#### Notes and features

• Tyre for professional use on lawns, gardens and golf courses.

15.11.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

### **Technical Informations**

| Item number                  | 19110132            |
|------------------------------|---------------------|
| EAN                          | 8994242015767       |
| Valid tyre size              | 16 x 6.50 - 8       |
| LI / SI / PR                 | 52 A6 / 64 A6, 4 PR |
| TL/TT                        | TT                  |
| SET                          | Tube                |
| Valve designation            | TR 13               |
| Ventilposition               | lateral             |
| Brand                        | Deli                |
| Tread pattern                | S-365               |
| Antistatic                   | No                  |
| Tyre colour                  | Black               |
| ECE regulation number        | ECE 106             |
| Nettogewicht [kg] (gültig)   | 3,12                |
| Recommended rim size         | 5.375               |
| Maximum air pressure [bar].  | 1,90                |
| Section width (mm)           | 170                 |
| Outer diameter of tyre [mm]. | 410                 |
| Stat. radius (SLR) [mm]      | 180                 |
| Rolling circumference [mm].  | 1201                |
| Tread depth (mm)             | 5,0                 |
| E-Ready                      | No                  |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 52 A6 | 200                | 30           | Drive Wheel   | 1,90                        |              |
| 64 A6 | 280                | 30           | Free Rolling  | 1,90                        |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.