Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	19110136	
Valid tyre size	16 x 6.50 - 8	
LI / SI / PR	52 A6 / 64 A6, 4 PR	
TL/TT	TL	
Brand	Deli	
Tread pattern	S-247	



Notes and features

• Agricultural tyre with traction tread pattern.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	19110136
EAN	8994242026633
Valid tyre size	16 × 6.50 - 8
LI / SI / PR	52 A6 / 64 A6, 4 PR
TL/TT	TL
Brand	Deli
Tread pattern	S-247
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	3,84
Recommended rim size	5.375
Maximum air pressure [bar].	1,90
Section width (mm)	160
Outer diameter of tyre [mm].	413
Stat. radius (SLR) [mm]	184
Rolling circumference [mm].	1229
Tread depth (mm)	12,7
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
52 A6	200	30	Drive Wheel	1,90	
64 A6	280	30	Free Rolling	1,90	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.