Bohnenkamp Moving Professionals

22.09.2024

TYRES

Product group	Tyres
Item number	19111100
Valid tyre size	10.0 / 80 - 12
LI / SI / PR	120 A8, 10 PR
TL/TT	TL
Brand	Deli
Tread pattern	SG-316



Notes and features

- Implement tyre for trailers and other agricultural machines such as spreaders, balers, ploughs, seeders, etc.
- Tread pattern design and rounded shoulder area ensure soil protection in fields and low rolling resistance on the road.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	19111100
EAN	8994242015477
Valid tyre size	10.0 / 80 - 12
LI / SI / PR	120 A8, 10 PR
TL/TT	TL
Brand	Deli
Tread pattern	SG-316
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	11,37
Recommended rim size	7.00
Maximum air pressure [bar].	3,90
Section width (mm)	252
Outer diameter of tyre [mm].	708
Stat. radius (SLR) [mm]	310
Rolling circumference [mm].	2122
Tread depth (mm)	7,6
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
120 A8	1400	40		3,90	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.