

TYRES

Product group	Tyres	
Item number	19111107	
Valid tyre size	7.50 - 10	
LI / SI / PR	111 A8, 12 PR	
TL/TT	тт	
Brand	Deli	
Tread pattern	SG-316	



Notes and features

- Implement tyre for trailers and other agricultural machines such as spreaders, balers, ploughs, seeders, etc.
- Tread pattern design and rounded shoulder area ensure soil protection in fields and low rolling resistance on the road.



Technical Informations

Item number	19111107
EAN	8994242018249
Valid tyre size	7.50 - 10
LI / SI / PR	111 A8, 12 PR
TL/TT	тт
Brand	Deli
Tread pattern	SG-316
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	9,80
Recommended rim size	6.00
Permitted rim size	5.50
Maximum air pressure [bar].	5,00
Section width (mm)	213
Outer diameter of tyre [mm].	648
Stat. radius (SLR) [mm]	289
Rolling circumference [mm].	1970
Tread depth (mm)	8,3
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
111 A8	1090	40		5,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.