

TYRES

Product group	Tyres
Item number	19111109
Valid tyre size	7.00 - 12
LI / SI / PR	95 A8, 6 PR
TL/TT	тт
Brand	Deli
Tread pattern	SG-316



Notes and features

- Implement tyre for trailers and other agricultural machines such as spreaders, balers, ploughs, seeders, etc.
- Tread pattern design and rounded shoulder area ensure soil protection in fields and low rolling resistance on the road.



Technical Informations

Item number	19111109
EAN	8994242026763
Valid tyre size	7.00 - 12
LI / SI / PR	95 A8, 6 PR
TL/TT	тт
Brand	Deli
Tread pattern	SG-316
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	8,66
Recommended rim size	5.00
Maximum air pressure [bar].	3,10
Section width (mm)	196
Outer diameter of tyre [mm].	684
Stat. radius (SLR) [mm]	306
Rolling circumference [mm].	2050
Tread depth (mm)	7,6
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
95 A8	690	40		3,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.