

TYRES

Product group	Tyres	
Item number	19111119	
Valid tyre size	26 x 12.00 - 12	
LI / SI / PR	100 A8 / 113 A8, 8 PR	
TL/TT	TL	
Brand	Deli	
Tread pattern	SG-818	



Notes and features

- The Deli SG-818 was specially developed for use on skid steer loaders and compact tractors.
- Its tractor pattern offers very good traction and excellent self-cleaning properties.
- Even on soft and muddy surfaces, the tyre offers very good performance.



Technical Informations

Item number	19111119
EAN	8994242027067
Valid tyre size	26 x 12.00 - 12
LI / SI / PR	100 A8 / 113 A8, 8 PR
TL/TT	TL
Brand	Deli
Tread pattern	SG-818
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	15,10
Recommended rim size	10.501
Maximum air pressure [bar].	2,10
Section width (mm)	316
Outer diameter of tyre [mm].	650
Stat. radius (SLR) [mm]	281
Rolling circumference [mm].	1942
Tread depth (mm)	15,2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
100 A8	800	40	Drive Wheel	2,10	
113 A8	1150	40	Free Rolling	2,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.