

TYRES

Product group	Tyres	
Item number	19111124	
Valid tyre size	11.5 / 80 - 15.3	
LI / SI / PR	139 A8, 14 PR	
TL/TT	TL	
Brand	Deli	
Tread pattern	Forestry 316	



Notes and features

- The Deli SG-316 Forestry Basic is a bias implement tyre featuring a very cut-resistant rubber compound.
- Its increased Shore hardness 70 enables it to be used as a forestry tyre.
- The special tread design and rounded shoulder area provide good driving characteristics.
- Ideal for light trailers.



Technical Informations

Item number	19111124
EAN	8994242027982
Valid tyre size	11.5 / 80 - 15.3
LI / SI / PR	139 A8, 14 PR
TL/TT	TL
Brand	Deli
Tread pattern	Forestry 316
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	20,60
Recommended rim size	9.00
Maximum air pressure [bar].	4,75
Section width (mm)	292
Outer diameter of tyre [mm].	870
Stat. radius (SLR) [mm]	382
Rolling circumference [mm].	2619
Tread depth (mm)	9,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
139 A8	2430	40		4,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.