

TYRES

| | |
|-----------------|------------------|
| Product group | Tyres |
| Item number | 19111125 |
| Valid tyre size | 11.5 / 80 - 15.3 |
| LI / SI / PR | 131 A8, 10 PR |
| TL/TT | TL |
| Brand | Deli |
| Tread pattern | SG-316 |



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- Implement tyre for trailers and other agricultural machines such as spreaders, balers, ploughs, seeders, etc.
- Tread pattern design and rounded shoulder area ensure soil protection in fields and low rolling resistance on the road.

Technical Informations

| | |
|------------------------------|------------------|
| Item number | 19111125 |
| EAN | 8994242016764 |
| Valid tyre size | 11.5 / 80 - 15.3 |
| LI / SI / PR | 131 A8, 10 PR |
| TL/TT | TL |
| Brand | Deli |
| Tread pattern | SG-316 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 18,45 |
| Recommended rim size | 9.00 |
| Maximum air pressure [bar]. | 3,40 |
| Section width (mm) | 290 |
| Outer diameter of tyre [mm]. | 864 |
| Stat. radius (SLR) [mm] | 383 |
| Rolling circumference [mm]. | 2601 |
| Tread depth (mm) | 9,5 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 131 A8 | 1950 | 40 | | 3,40 | |