

TYRES

Product group	Tyres	
Item number	19111137	
Valid tyre size	380 / 55 - 17	
LI / SI / PR	138 A8 / 134 B, 12 PR	
TL/TT	TL	
Brand	Deli	
Tread pattern	SG-316	



Notes and features

- Implement tyre for trailers and other agricultural machines such as spreaders, balers, ploughs, seeders, etc.
- Tread pattern design and rounded shoulder area ensure soil protection in fields and low rolling resistance on the road.



Technical Informations

Item number	19111137
EAN	8994242016856
Valid tyre size	380 / 55 - 17
Alternative size 1	15.0/55-17
LI / SI / PR	138 A8 / 134 B, 12 PR
TL/TT	TL
Brand	Deli
Tread pattern	SG-316
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	26,62
Recommended rim size	13
Maximum air pressure [bar].	2,80
Section width (mm)	384
Outer diameter of tyre [mm].	850
Stat. radius (SLR) [mm]	363
Rolling circumference [mm].	2522
Tread depth (mm)	10,4
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
138 A8	2360	40	Free Rolling	2,80	
134 B	2120	50	Free Rolling	2,80	
	2810	25	Free Rolling	3,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.