

## **TYRES**

Product group	Tyres
Item number	19111140
Valid tyre size	315 / 80 - 18
LI / SI / PR	143 A8, 12 PR
TL/TT	TL
Brand	Deli
Tread pattern	SG-316





## Notes and features

- Implement tyre for trailers and other agricultural machines such as spreaders, balers, ploughs, seeders, etc.
- Tread pattern design and rounded shoulder area ensure soil protection in fields and low rolling resistance on the road.



## **Technical Informations**

Item number	19111140
EAN	8994242016849
Valid tyre size	315 / 80 - 18
Alternative size 1	12.5/80-18
LI / SI / PR	143 A8, 12 PR
TL/TT	TL
Brand	Deli
Tread pattern	SG-316
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	26,96
Recommended rim size	10
Permitted rim size	9, 11
Maximum air pressure [bar].	3,20
Section width (mm)	308
Outer diameter of tyre [mm].	961
Stat. radius (SLR) [mm]	417
Rolling circumference [mm].	2825
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 A8	2725	40		3,20	
	3750	10		3,20	
	4000	5		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.