

TYRES

Product group	Tyres	
Item number	19111144	
Valid tyre size	400 / 50 - 15	
LI / SI / PR	109 A8 / 121 A8, 10 PR	
TL/TT	TL	
Brand	Deli	
Tread pattern	SG-818	





Notes and features

- The Deli SG-818 was specially developed for use on skid steer loaders and compact tractors.
- Its tractor pattern offers very good traction and excellent self-cleaning properties.
- Even on soft and muddy surfaces, the tyre offers very good performance.



Technical Informations

Item number	19111144
EAN	8994242026671
Valid tyre size	400 / 50 - 15
Alternative size 1	31x15.50-15
LI / SI / PR	109 A8 / 121 A8, 10 PR
TL/TT	TL
Brand	Deli
Tread pattern	SG-818
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	25,00
Recommended rim size	13LB, 13.00LB
Maximum air pressure [bar].	3,00
Section width (mm)	383
Outer diameter of tyre [mm].	777
Rolling circumference [mm].	2300
Tread depth (mm)	17,9
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
109 A8	1030	40	Drive Wheel	3,00	
121 A8	1450	40	Free Rolling	3,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.