Bohnenkamp Moving Professionals

19.09.2024

TYRES

Product group	Tyres	
Item number	19166110	
Valid tyre size	5.70 / 5.00 - 8	
LI / SI / PR	77 M, 6 PR	
TL/TT	TL	
Brand	Deli	
Tread pattern	S-378	



Notes and features

- The S-378 is a versatile and extremely reliable highspeed car trailer tyre.
- Due to its increased number of plies, the tyre offers a high load capacity.
- Its strong and robust casing offers perfect rolling behaviour under load at normal speeds.
- Particularly suitable for small to medium-sized boat and camping trailers.

Bohnenkamp Moving Professionals

Technical Informations

Item number	19166110
EAN	8994242014975
Valid tyre size	5.70 / 5.00 - 8
LI / SI / PR	77 M, 6 PR
TL/TT	TL
Brand	Deli
Tread pattern	S-378
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 30
Nettogewicht [kg] (gültig)	3,44
Recommended rim size	3.75
Permitted rim size	3.00
Maximum air pressure [bar].	5,30
Section width (mm)	140
Outer diameter of tyre [mm].	465
Stat. radius (SLR) [mm]	218
Rolling circumference [mm].	1425
Tread depth (mm)	5,4
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
77 M	412	130		5,30	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.