

TYRES

Product group	Tyres
Item number	19172432
Valid tyre size	400 / 60 - 15.5
LI / SI / PR	152 A8, 18 PR
TL/TT	TL
Brand	Deli
Tread pattern	SG-316



Notes and features

- Implement tyre for trailers and other agricultural machines such as spreaders, balers, ploughs, seeders, etc.
- Tread pattern design and rounded shoulder area ensure soil protection in fields and low rolling resistance on the road.



Technical Informations

Item number	19172432
EAN	8994242026701
Valid tyre size	400 / 60 - 15.5
LI / SI / PR	152 A8, 18 PR
TL/TT	TL
Brand	Deli
Tread pattern	SG-316
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	29,43
Recommended rim size	13.00
Maximum air pressure [bar].	5,00
Section width (mm)	396
Outer diameter of tyre [mm].	870
Stat. radius (SLR) [mm]	374
Rolling circumference [mm].	2578
Tread depth (mm)	10,4
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 A8	3550	40		5,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.