

## TYRES

Product group	Tyres
Item number	19172455
Valid tyre size	400 / 55 R 17
LI / SI / PR	152 D
TL/TT	TL
Brand	Starco
Tread pattern	GU-783 HS Flotation



## Notes and features

- The Starco GU-783 is a flotation radial tyre for agricultural trailers and tillage equipment.
- Due to its particularly soil-friendly tread pattern, the tyre is also very suitable for use in grassland.
- Its large contact area and low inflation pressure ensure low soil compaction.
- The tyre is particularly suitable for applications where road transport and work in the field are equally necessary.
- It is approved for speeds of up to 65 km/h.

## Technical Informations

Item number	19172455
EAN	5707562656373
Valid tyre size	400 / 55 R 17
LI / SI / PR	152 D
TL/TT	TL
Brand	Starco
Tread pattern	GU-783 HS Flotation
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	30,70
Recommended rim size	13.00
Maximum air pressure [bar].	5,00
Section width (mm)	410
Outer diameter of tyre [mm].	882
Stat. radius (SLR) [mm]	380
Rolling circumference [mm].	2714
Tread depth (mm)	10,4
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 D	3550	65	Free Rolling	5,00	
			Drive Wheel	5,00	