

TYRES

Product group	Tyres	
Item number	19172460	
Valid tyre size	400 / 45 L - 17.5	
LI / SI / PR	156 B	
TL/TT	TL	
Brand	Deli	
Tread pattern	SG-815	



Notes and features

- The Deli SG-815 is an implement tyre for use on agricultural trailers and other towed vehicles like balers and manure spreaders.
- Its grooved tread pattern offers very good handling characteristics in the field and also when driving on the road.
- Its rib pattern provides smooth riding in the field and also on road transportations.
- The wide contact area and the low tread pattern reduce soil compaction.



Technical Informations

Item number	19172460
EAN	8994242026664
Valid tyre size	400 / 45 L - 17.5
LI / SI / PR	156 B
TL/TT	TL
Brand	Deli
Tread pattern	SG-815
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	46,15
Recommended rim size	14.00
Permitted rim size	13.00
Maximum air pressure [bar].	6,00
Section width (mm)	392
Outer diameter of tyre [mm].	770
Stat. radius (SLR) [mm]	348
Rolling circumference [mm].	2285
Tread depth (mm)	13,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 B	4000	50		6,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.