Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	19210101
Valid tyre size	AT 16 x 8 - 7
LI / SI / PR	28 F, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K570



Notes and features

• ATV and quad tyre.

The specific arrangement of the lugs ensures good • traction in off-road applications.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	19210101
EAN	5707562265414
Valid tyre size	AT 16 x 8 - 7
Alternative size 1	165/65-7
LI / SI / PR	28 F, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K570
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	2,75
Recommended rim size	5.20
Maximum air pressure [bar].	0,70
Section width (mm)	170
Outer diameter of tyre [mm].	403
Tread depth (mm)	9,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
28 F	100	80		0,70	