

TYRES

Product group	Tyres	
Item number	19210112	
Valid tyre size	AT 20 x 7 - 8	
LI / SI / PR	23 N, 4 PR	
TL/TT	TL	
Brand	Kenda	
Tread pattern	K546F Speed Racer	



Notes and features

- The Kenda K546F Speed Racer is an ATV tyre for use as a racing tyre on hard surfaces.
- However, it is just as suitable for vehicles used to maintain lawns.
- The tyre offers very good self-cleaning in all possible applications.
- When used as a sports tyre on the road, the tyre is particularly suitable for the front axle.
- The ideal addition for the rear axle is the K547 Speed Racer.



Technical Informations

Item number	19210112
EAN	5707562259499
Valid tyre size	AT 20 x 7 - 8
Alternative size 1	175/85-8
LI / SI / PR	23 N, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K546F Speed Racer
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	6,02
Recommended rim size	5.5
Maximum air pressure [bar].	0,35
Section width (mm)	188
Outer diameter of tyre [mm].	498
Tread depth (mm)	9,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
23 N	87,5	140		0,35	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.