Bohnenkamp Moving Professionals

16.11.2024

TYRES

Product group	Tyres
Item number	19210170
Valid tyre size	23 x 8.00 - 11
LI / SI / PR	33 F, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K299 Bearclaw



Notes and features

• Universal ATV and quad tyre.

• The specific arrangement of the lugs ensures good traction off-road.

Bohnenkamp Moving Professionals

Technical Informations

Iten number19210170EAN507562129068Valid tyre size32 x 8.00 - 11Altenative size 1195/80-11Altenative size 1195/80-11LI SJ / PR33 F, 4 PRTLTTT.BrandKendaTread patternK299 BearclawAntistaticNoFCE regulation numberCE 54Recommended rim size5.5Antiogenicity [Sg / Gg3.5Recommended rim size3.5Action with (mm)3.6Beach3.5Ceread pattern3.5Antiogenicity [Sg / Gg3.5Antiogenicity [Sg / Gg3.5Antion and pressure [ba]3.6Action differenticity [Sg / Gg3.5Action differenticity [Sg / Gg3.5Act		
Valid tyre sizeJakanana (Jakana)Valid tyre size23 x 8.00 · 11Alternative size 1195/80 · 11Li / Si / PR33 F, 4 PRTLTTTBrandKendaTread patternK299 BearclawAntistaticNoTyre colourBlackBecomended rim size5.5Atsimum air pressure [bai]0.3Section vidth (mm)187Guter diameter of tyre [mm]8.6Tread pattern6.5Antistatic0.3Antistatic0.3Back0.3 <trr>Back0</trr>	Item number	19210170
Alternative size 1195/80-11Alternative size 1195/80-11LI/SI/PR33 F, 4 PRTL/TTTLBrandKendaBrandKendaTread patternK299 BearclawAntistaticNoCyre colourBlackBickCE 54Retogewicht [kg] (gült)7,54Recommended rim size0.3Section width (mm)86Outer diameter of tyre [mm]86Tread depth (mm)86	EAN	5707562129068
LI / SI / PR33 F, 4 PRTL/TTLTL/TTLBrandKendaKendaKendaTread patternK29 BearclawAntistaticNoBlackECE Foreulation numberFCE regulation numberECE 54Nettogewicht [kg] (gültig)7,54Recommended rim size0,35Section width (mm)566Otter diameter of tyre [mm]540Tead depth (mm)14,5	Valid tyre size	23 x 8.00 - 11
TLTTIITLTTIIBrandKendaTread patternS29 BearclawAntistaticNoJeacBackTre colourBickBickS29 SearclawNettogewicht [kg] (ditig)S4Attistation numberS5Attigewicht [kg] (ditig)S1Schonnended rim sizeS3Otter diameter of tyre (m)S6Tread depth (m)S4	Alternative size 1	195/80-11
BrandKendaBrandKendaTread patternK299 BearclawAntistaticNoFyre colourBlackECE regulation numberECE 54Nettogewicht [kg] (gült)7,54Recommended rim size0.3Saction width (mm)187Stotion width (mm)86Late of the function14,5	LI / SI / PR	33 F, 4 PR
Tread patternK299 BearclawAntistaticNoTyre colourBlackECE regulation numberECE 54Nettogewicht [kg] (gültig)7,54Recommended rim size6.5Section width (mm)197Section tyre [main586Tread depth (nm)14,5	TL/TT	TL
AntistaticNoTyre colourBlackECE regulation numberECE 54Nettogewicht [kg] (gültig)7,54Recommended rim size6,5Maxinum air pressure [ba]0,35Section width (mm)187Outer diameter of tyre [mm]566Tread depth (mm)14,5	Brand	Kenda
Tyre colourBackECE regulation numberECE 54Nettogewicht [kg] (gültig)7,54Recommended rim size6.5Maxinum air pressure [bas]0,35Section width (mm)187Subschleit [bas]586Tread depth (mm)4.5	Tread pattern	K299 Bearclaw
ECE regulation numberECE 54Nettogewicht [kg] (gültig)7,54Recommended rim size6,5Maximum air pressure [bar]0,35Section width (mm)187Outer diameter of tyre [mm]586Tread depth (mm)14,5	Antistatic	No
Nettogewicht [kg] (gültig)7,54Recommended rim size6.5Maximum air pressure [bar]0,35Section width (mm)187Outer diameter of tyre [mm]586Tread depth (mm)14,5	Tyre colour	Black
Recommended rim size6.5Maximum air pressure [bar]0,35Section width (mm)187Outer diameter of tyre [mm]586Tread depth (mm)14,5	ECE regulation number	ECE 54
Maximum air pressure [bar]. 0,35 Section width (mm) 187 Outer diameter of tyre [mm]. 586 Tread depth (mm) 14,5	Nettogewicht [kg] (gültig)	7,54
Section width (mm) 187 Outer diameter of tyre [mm]. 586 Tread depth (mm) 14,5	Recommended rim size	6.5
Outer diameter of tyre [mm]. 586 Tread depth (mm) 14,5	Maximum air pressure [bar].	0,35
Tread depth (mm) 14,5	Section width (mm)	187
	Outer diameter of tyre [mm].	586
E-Ready No	Tread depth (mm)	14,5
	E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
33 F	115	80		0,35	