Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	19210186
Valid tyre size	AT 25 x 8 - 12
LI / SI / PR	38 N, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K572 Road Go



Notes and features

• ATV and quad tyre.

• Particularly suitable for road use.

Bohnenkamp Moving Professionals

Technical Informations

Iten number1920186EAN507562271040Valid tyre sizeA 72 5 x 8 - 12Atenative size 1205/80-12L 1 SJ / PR30 N.4 PRTLTTTLFrandKondaTread patternKo72 Road GoAritstaicNoECE regulation numberECE 54Redugewicht [kg] (güll)7.06Retormender im size0.34Getton width (mm)0.34Getton width (mm)0.34Farad pattern0.30Retormender im size0.30Retormender im size0.34Face multing im size (mm)0.34Face multing im size (mm)0.34<		
Valid tyre sizeAT 25 × 8 · 12Aternative size 1205/80-12Li / Si / PR38 N, 4 PRT_LTTTBrandKendaTread patternK57 Road GoAftistaticNoTyre colourBlackBecomended rim size7.0No.7.0Becomended rim size0.3Outer diameter of tyre (m)0.3Outer diameter of tyre (m)	Item number	19210186
Aternative size 1205/80-12Alternative size 1205/80-12L/ SI / PR38 N, 4 PRTLTTTLBrandKendaTread patternK572 Road GoAntistaticNoConstructionBlackEce 54ConstructionRetogewicht [kg] (gilli)7.0Anismun air pressure [back3.0Construction3.0Cons	EAN	5707562271040
LI / SI / PRSi / A PRTL/TTTLFradTLBrandKondaTread patternK572 Road GoAntistaticNoBackEce Fagulation numberBCE regulation numberSi / Si /	Valid tyre size	AT 25 x 8 - 12
TLTTIITLTTIIFradKedaFradpatternK57 Road GoAntistaticNoTyreolourBiackECE regulation numberCE 54Netogewicht [kg] (dit)JoActomating in SameJoRecommender in seeJoBackSameDiter damenter functionJoSection width (mm)JoSection width (mm)JoDiter damenter functionJoSection width (mm)JoSection width (mm)JoSectio	Alternative size 1	205/80-12
BrandKendaTread patternK572 Road GoAntistaticNoTyre colourBlackECE regulation numberECE 54Nettogewich [kg] (gül tag)7.0Recommended rim size0.3Gate1.0Section width (mm)0.3Get fagulation0.3Berton (mm)0.3Berton (mm)0.3Date (mm)	LI / SI / PR	38 N, 4 PR
Tread patternK572 Road GoAntistaticNoTyre colourBlackECE regulation numberECE 54Nettogewicht [kg] (giltig)7,06Recommended rim size0,34Section width (mm)10Section tripter (mm)625Outer diameter of tyre (mm)9,0	TL/TT	TL
AntistaticNoTyre colourBackECE regulation numberECE 54Nettogewicht [kg] (gültig)7,06Recommended rim size7,0Maxinum air pressure [ba]0,34Section width (mm)210Outer diameter of tyre [mm]9,0	Brand	Kenda
Tyre colourBlackECE regulation numberCCE 54Nettogewicht [kg] (gültig)7,06Recommended rim size0,34Section width (mm)0,34Section tyre [mm]0,20Duter diameter of tyre [mm]9,0	Tread pattern	K572 Road Go
ECE regulation numberECE 54Nettogewicht [kg] (gültig)7,06Recommended rim size7,0Maxinum air pressure [bar]0,34Section width (mm)210Outer diameter of tyre [mm]0,9Maxinum air meter of tyre [mm]0,0	Antistatic	No
Nettogewicht [kg] (gültig)7,06Recommended rim size7.0Maximum air pressure [bar]0,34Section width (mm)210Outer diameter of tyre [mm]625Tread depth (mm)9,0	Tyre colour	Black
Recommended rim size7.0Maximum air pressure [bar]0.34Section width (mm)210Outer diameter of tyre [mm]625Tread depth (mm)9.0	ECE regulation number	ECE 54
Maximum air pressure [bar]. 0,34 Section width (mm) 210 Outer diameter of tyre [mm]. 625 Tread depth (mm) 9,0	Nettogewicht [kg] (gültig)	7,06
Section width (mm) 210 Outer diameter of tyre [mm] 625 Tread depth (mm) 9,0	Recommended rim size	7.0
Outer diameter of tyre [mm]. 625 Tread depth (mm) 9,0	Maximum air pressure [bar].	0,34
Tread depth (mm) 9,0	Section width (mm)	210
	Outer diameter of tyre [mm].	625
E-Ready No	Tread depth (mm)	9,0
	E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
38 N	132	140		0,34	