Bohnenkamp Moving Professionals

TYRES

| Product group | Tyres | |
|-----------------|------------------|--|
| Item number | 19210208 | |
| Valid tyre size | AT 28 x 11 - 14 | |
| LI / SI / PR | 58 L, 6 PR | |
| TL/TT | TL | |
| Brand | Kenda | |
| Tread pattern | K538 Executioner | |



Notes and features

• ATV and quad tyre.

• The specific arrangement of the lugs ensures good traction in off-road applications.

Bohnenkamp Moving Professionals

Technical Informations

| Item number | 19210208 |
|------------------------------|------------------|
| EAN | 4717954446841 |
| Valid tyre size | AT 28 x 11 - 14 |
| Alternative size 1 | 265/65-14 |
| LI / SI / PR | 58 L, 6 PR |
| TL/TT | TL |
| Brand | Kenda |
| Tread pattern | K538 Executioner |
| Star Rating | *** |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 75 |
| Nettogewicht [kg] (gültig) | 14,72 |
| Recommended rim size | 8.0 |
| Permitted rim size | 8.5, 9.0 |
| Maximum air pressure [bar]. | 0,50 |
| Section width (mm) | 263 |
| Outer diameter of tyre [mm]. | 708 |
| Tread depth (mm) | 29,5 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 58 L | 236 | 120 | | 0,50 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.