Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	19211079
Valid tyre size	4.00 - 4
LI / SI / PR	48 A4 / 59 A4, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K373



Notes and features

- All-purpose small tyre with block tread pattern.
- The tyre is particularly suitable for transport equipment.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	19211079
EAN	5707562329611
Valid tyre size	4.00 - 4
LI / SI / PR	48 A4 / 59 A4, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K373
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	1,26
Recommended rim size	3.0
Permitted rim size	2.25C, 2.10A
Maximum air pressure [bar].	4,10
Section width (mm)	121
Outer diameter of tyre [mm].	306
Rolling circumference [mm].	913
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
48 A4	180	20	Drive Wheel	4,10	
59 A4	243	20	Free Rolling	4,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.