

TYRES

Product group	Tyres	
Item number	19211085	
Valid tyre size	4.10 / 3.50 - 4	
LI / SI / PR	32 A4 / 43 A4, 4 PR	
TL/TT	TL	
Brand	Kenda	
Tread pattern	K500 Super Turf	



Notes and features

- For professional use on lawns.
- Very good wear properties and increased puncture resistance.
- The rounded tyre shoulder prevents lawn damage.



Technical Informations

Item number	19211085
EAN	5707562130194
Valid tyre size	4.10 / 3.50 - 4
LI / SI / PR	32 A4 / 43 A4, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K500 Super Turf
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	0,98
Recommended rim size	2.75
Maximum air pressure [bar].	3,50
Section width (mm)	95
Outer diameter of tyre [mm].	272
Rolling circumference [mm].	812
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
32 A4	112	20	Drive Wheel	3,50	
43 A4	155	20	Free Rolling	3,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.