

TYRES

Product group	Tyres
Item number	19211115
Valid tyre size	3.50 - 6
LI / SI / PR	33 A4 / 44 A4, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K357A



Notes and features

Versatile traction tyre.

• Ideal for use on compact tractors and single-axle tractors.



Technical Informations

Item number	19211115
EAN	5707562129662
Valid tyre size	3.50 - 6
LI / SI / PR	33 A4 / 44 A4, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K357A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	1,70
Recommended rim size	3.50
Permitted rim size	2.50
Maximum air pressure [bar].	2,90
Section width (mm)	94
Outer diameter of tyre [mm].	340
Rolling circumference [mm].	1015
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
33 A4	115	20	Drive Wheel	2,90	
44 A4	160	20	Free Rolling	2,90	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.