Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	19211125	
Valid tyre size	13 x 6.50 - 6	
LI / SI / PR	42 A4 / 53 A4, 4 PR	
TL/TT	TT	
SET	Tube	
Brand	Kenda	
Tread pattern	K358 Turf Rider	



Notes and features

• Tyre for professional use on lawns, gardens and golf courses.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	19211125
EAN	5707562330204
Valid tyre size	13 × 6.50 - 6
LI / SI / PR	42 A4 / 53 A4, 4 PR
TL/TT	ТТ
SET	Tube
Valve designation	TR 13
Ventilposition	lateral
Brand	Kenda
Tread pattern	K358 Turf Rider
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	2,28
Recommended rim size	4.50
Maximum air pressure [bar].	1,90
Section width (mm)	154
Outer diameter of tyre [mm].	328
Rolling circumference [mm].	979
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
42 A4	150	20	Drive Wheel	1,90	
53 A4	206	20	Free Rolling	1,90	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.