

TYRES

Product group	Tyres
Item number	19211144
Valid tyre size	165 / 65 - 8
LI / SI / PR	58 G, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K399 Pro Tour



Notes and features

- The Kenda K399 Pro Tour in this dimension is a diagonal ply tyre for city carts.
- Thanks to its wide contact area, it provides excellent traction on paved paths and roads.
- The tyre offers high ride comfort and low rolling resistance.



Technical Informations

Item number	19211144
EAN	4040658081675
Valid tyre size	165 / 65 - 8
Alternative size 1	16x6.50-8
LI / SI / PR	58 G, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K399 Pro Tour
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 75
Nettogewicht [kg] (gültig)	3,78
Recommended rim size	5.375
Maximum air pressure [bar].	2,40
Section width (mm)	167
Outer diameter of tyre [mm].	415
Stat. radius (SLR) [mm]	182
Rolling circumference [mm].	1265
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
58 G	236	90		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.