

TYRES

Product group	Tyres	
Item number	19211145	
Valid tyre size	15 x 5.00 - 6	
LI / SI / PR	37 A4 / 50 A4, 2 PR	
TL/TT	TL	
Brand	Kenda	
Tread pattern	K478	



Notes and features

- The Kenda K478 was developed for use on snow blowers and similar equipment.
- It provides exceptional traction on slush, snow and ice.



Technical Informations

Item number	19211145
EAN	4040658081682
Valid tyre size	15 x 5.00 - 6
Alternative size 1	130/85-6
LI / SI / PR	37 A4 / 50 A4, 2 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K478
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	2,74
Recommended rim size	3.50
Maximum air pressure [bar].	1,20
Section width (mm)	131
Outer diameter of tyre [mm].	375
Rolling circumference [mm].	1119
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
37 A4	128	20	Drive Wheel	1,20	
50 A4	190	20	Free Rolling	1,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.