Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	19211163	
Valid tyre size	3.50 - 8	
LI / SI / PR	38 A4 / 49 A4, 4 PR	
TL/TT	TL	
Brand	Kenda	
Tread pattern	K357	



Notes and features

• Versatile traction tyre.

• Ideal for use on compact tractors and single-axle tractors.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	19211163
EAN	5707562129709
Valid tyre size	3.50 - 8
LI / SI / PR	38 A4 / 49 A4, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K357
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	2,34
Recommended rim size	2.50A
Maximum air pressure [bar].	2,80
Section width (mm)	90
Outer diameter of tyre [mm].	384
Rolling circumference [mm].	1146
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
38 A4	132	20	Drive Wheel	2,80	
49 A4	185	20	Free Rolling	2,80	